

Bright steel

Round bar according to DIN EN 10277, tolerance according to DIN EN 10278 Bar length approx. 3 m or approx. 6 m

Stock availability marked with a dot; other dimensions available at short notice. Additional sizes, formats, and grades available on request.

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)	C35+C/SH (C35K)	C45+C/SH (C45K)	C45+SL geschliffen h6	11SMn30+C/SH (9SMn28K)	11SMnPb30+C/SH (9SMnPb28K)	42CrMo4V +C/SH	16MnCr5 +C/SH
2									
3									
4	●								
5	●								
6	●								
7									
8	●								
10	●	●		●	●	●	●	●	●
12	●	●		●	●	●	●	●	●
14									
15	●	●		●	●	●	●	●	●
16									
18									
20	●	●		●	●			●	●
22						●	●		
24									
25	●	●		●	●	●	●	●	●
27									
28									
30	●	●		●	●	●	●	●	●
32									
35	●	●		●	●				

Continuation on page 2

Continuation - Round bar according to DIN EN 10277, tolerance according to DIN EN 10278 Bar length approx. 3 m or approx. 6 m

Stock availability marked with a dot; other dimensions available at short notice. Additional sizes, formats, and grades available on request.

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)	C35+C/SH (C35K)	C45+C/SH (C45K)	C45+SL geschliffen h6	11SMn30 +C/SH (9SMn28K)	11SMnPb30 +C/SH (9SMnPb28K)	42CrMo4V +C/SH	16MnCr5 +C/SH
36									
40	●	●		●	●	●	●	●	●
42									
45									
50	●	●		●	●	●	●	●	●
55									
60	●	●		●	●			●	●
65									
70	●	●		●	●				
75									
80	●	●		●	●				
85									
90	●	●		●	●				
100	●	●		●	●				
110									
120									
130									
140									
150									

Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m /6 m

Stock availability marked with a dot; other dimensions available at short notice. Additional sizes, formats, and grades available on request.

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
5 x 2,0		
5 x 2,5		
5 x 3,0		
5 x 4,0		
6 x 2,0		
6 x 2,5		
6 x 3,0		
6 x 4,0		
7 x 2,0		
7 x 2,5		
7 x 3,0		
7 x 4,0		
7 x 5,0		
7 x 6,0		
8 x 2,0		
8 x 2,5		
8 x 3,0		
8 x 4,0		
8 x 5,0		
8 x 6,0		
8 x 7,0		
9 x 2,0		
9 x 2,5		
9 x 3,0		
9 x 4,0		
9 x 5,0		
9 x 6,0		
9 x 7,0		
10 x 2,0		
10 x 2,5		
10 x 4,0	●	
10 x 5,0	●	
10 x 7,0		
10 x 8,0		
11 x 2,0		
11 x 2,5		
11 x 3,0		
11 x 4,0		

Continuation on page 4

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m /6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
11 x 5,0		
11 x 6,0		
11 x 7,0		
11 x 8,0		
12 x 2,0		
12 x 2,5		
12 x 7,0		
13 x 2,0		
13 x 2,5		
13 x 3,0		
13 x 4,0		
13 x 5,0		
13 x 6,0		
13 x 7,0		
13 x 8,0		
14 x 2,0		
14 x 2,5		
14 x 3,0		
14 x 4,0		
14 x 5,0		
14 x 6,0		
14 x 7,0		
14 x 8,0		
14 x 10,0		
14 x 12,0		
15 x 2,0		
15 x 2,5		
15 x 4,0		
15 x 5,0	●	
15 x 7,0		
15 x 13,0		
16 x 2,0		
16 x 2,5		
16 x 3,0		
16 x 4,0		
16 x 5,0		
16 x 7,0		
16 x 8,0		

Continuation on page 5

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m /6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
16 x 12,0		
16 x 13,0		
16 x 14,0		
18 x 2,0		
18 x 2,5		
18 x 3,0		
18 x 4,0		
18 x 5,0		
18 x 6,0		
18 x 8,0		
18 x 12,0		
18 x 13,0		
18 x 14,0		
18 x 15,0		
18 x 16,0		
20 x 2,0		
20 x 2,5		
20 x 3,0	●	
20 x 4,0	●	
20 x 5,0	●	
20 x 7,0		
20 x 8,0	●	
20 x 10,0	●	
20 x 14,0		
20 x 15,0	●	
20 x 16,0		
20 x 18,0		
22 x 2,0		
22 x 2,5		
22 x 3,0		
22 x 4,0		
22 x 5,0		
22 x 6,0		
22 x 7,0		
22 x 8,0		
22 x 10,0		
22 x 12,0		
22 x 14,0		

Continuation on page 6

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
22 x 15,0		
22 x 16,0		
22 x 18,0		
24 x 2,0		
24 x 2,5		
24 x 3,0		
24 x 4,0		
24 x 5,0		
24 x 6,0		
24 x 8,0		
24 x 10,0		
24 x 12,0		
24 x 14,0		
24 x 15,0		
24 x 16,0		
24 x 18,0		
24 x 20,0		
25 x 2,0		
25 x 2,5		
25 x 3,0	●	
25 x 4,0	●	
25 x 5,0	●	
25 x 7,0		
25 x 10,0	●	
25 x 13,0		
25 x 14,0		
25 x 16,0		
25 x 18,0		
25 x 22,0		
26 x 2,0		
26 x 2,5		
26 x 3,0		
26 x 4,0		
26 x 5,0		
26 x 6,0		
26 x 8,0		
26 x 10,0		
26 x 12,0		

Continuation on page 7

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
26 x 13,0		
26 x 20,0		
28 x 2,0		
28 x 2,5		
28 x 3,0		
28 x 4,0		
28 x 5,0		
28 x 6,0		
28 x 7,0		
28 x 8,0		
28 x 10,0		
28 x 12,0		
28 x 14,0		
28 x 15,0		
28 x 16,0		
28 x 18,0		
28 x 20,0		
28 x 25,0		
30 x 2,0		
30 x 2,5		
30 x 3,0	●	
30 x 4,0	●	
30 x 5,0	●	
30 x 7,0		
30 x 10,0	●	
30 x 13,0		
30 x 14,0		
30 x 16,0		
30 x 18,0		
30 x 22,0		
32 x 2,0		
32 x 2,5		
32 x 3,0		
32 x 4,0		
32 x 5,0		
32 x 6,0		
32 x 7,0		
32 x 8,0		

Continuation on page 8

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
32 x 10,0		
32 x 12,0		
32 x 13,0		
32 x 14,0		
32 x 15,0		
32 x 16,0		
32 x 18,0		
32 x 20,0		
32 x 25,0		
35 x 2,0		
35 x 2,5		
35 x 3,0		
35 x 4,0		
35 x 7,0		
35 x 14,0		
35 x 16,0		
35 x 18,0		
35 x 25,0		
35 x 30,0		
36 x 2,0		
36 x 2,5		
36 x 3,0		
36 x 4,0		
36 x 5,0		
36 x 6,0		
36 x 8,0		
36 x 10,0		
36 x 12,0		
36 x 15,0		
36 x 16,0		
36 x 20,0		
36 x 25,0		
40 x 2,0		
40 x 2,5		
40 x 3,0	●	
40 x 4,0	●	
40 x 5,0	●	
40 x 6,0	●	

Continuation on page 9

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
40 x 7,0		
40 x 10,0	●	
40 x 13,0		
40 x 14,0		
40 x 16,0		
40 x 18,0		
40 x 20,0	●	
40 x 22,0		
40 x 35,0		
45 x 2,0		
45 x 2,5		
45 x 3,0		
45 x 4,0		
45 x 5,0		
45 x 6,0		
45 x 7,0		
45 x 8,0		
45 x 12,0		
45 x 15,0		
45 x 16,0		
45 x 18,0		
45 x 20,0		
45 x 22,0		
45 x 25,0		
45 x 30,0		
45 x 32,0		
45 x 35,0		
45 x 40,0		
50 x 2,0		
50 x 2,5		
50 x 3,0		
50 x 4,0		

Continuation on page 10

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
50 x 5,0	●	
50 x 6,0	●	
50 x 7,0		
50 x 8,0		
50 x 10,0		
50 x 12,0		
50 x 13,0		
50 x 14,0		
50 x 15,0		
50 x 16,0		
50 x 18,0		
50 x 20,0		
50 x 22,0		
50 x 25,0		
50 x 30,0		
50 x 32,0		
50 x 35,0		
50 x 40,0		
50 x 45,0		
55 x 2,0		
55 x 2,5		
55 x 3,0		
55 x 4,0		
55 x 5,0		
55 x 6,0		
55 x 7,0		
55 x 8,0		
55 x 10,0		
55 x 12,0		
55 x 15,0		
55 x 16,0		
55 x 18,0		
55 x 20,0		
55 x 25,0		
55 x 30,0		
55 x 45,0		
56 x 2,0		
56 x 2,5		

56 x 3,0

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
56 x 4,0		
56 x 6,0		
56 x 7,0		
56 x 8,0		
56 x 10,0		
56 x 12,0		
56 x 15,0		
56 x 16,0		
56 x 20,0		
56 x 25,0		
60 x 2,0		
60 x 2,5		
60 x 3,0		
60 x 4,0		
60 x 5,0	●	
60 x 6,0	●	
60 x 7,0		
60 x 8,0		
60 x 10,0	●	
60 x 12,0		
60 x 14,0		
60 x 15,0		
60 x 16,0		
60 x 18,0		
60 x 20,0		
60 x 25,0		
60 x 30,0		
60 x 32,0		
60 x 35,0		
60 x 40,0		
60 x 45,0		
60 x 50,0		
63 x 2,0		
63 x 2,5		
63 x 3,0		
63 x 4,0		
63 x 5,0		
63 x 6,0		

Continuation on page 12

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m /6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
63 x 8,0		
63 x 10,0		
63 x 12,0		
63 x 15,0		
63 x 16,0		
63 x 20,0		
63 x 25,0		
63 x 32,0		
63 x 40,0		
65 x 2,0		
65 x 2,5		
65 x 3,0		
65 x 4,0		
65 x 5,0		
65 x 6,0		
65 x 8,0		
65 x 10,0		
65 x 12,0		
65 x 13,0		
65 x 14,0		
65 x 15,0		
65 x 16,0		
65 x 20,0		
65 x 25,0		
65 x 30,0		
65 x 35,0		
65 x 40,0		
70 x 2,0		
70 x 2,5		
70 x 3,0		
70 x 4,0		
70 x 5,0		
70 x 6,0		
70 x 7,0		
70 x 8,0		
70 x 10,0		
70 x 12,0		
70 x 14,0		

Continuation on page 13

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m /6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
70 x 15,0		
70 x 16,0		
70 x 18,0		
70 x 20,0		
70 x 25,0		
70 x 30,0		
70 x 32,0		
70 x 35,0		
70 x 40,0		
70 x 45,0		
70 x 50,0		
70 x 60,0		
75 x 3,0		
75 x 4,0		
75 x 5,0		
75 x 6,0		
75 x 8,0		
75 x 10,0		
75 x 12,0		
75 x 13,0		
75 x 15,0		
75 x 16,0		
75 x 20,0		
75 x 25,0		
75 x 30,0		
80 x 3,0		
80 x 4,0		
80 x 5,0	●	
80 x 6,0	●	
80 x 7,0		
80 x 8,0		
80 x 10,0	●	
80 x 12,0		
80 x 15,0		
80 x 16,0		
80 x 20,0		
80 x 22,0		
80 x 25,0		

Continuation on page 14

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m /6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
80 x 30,0		
80 x 32,0		
80 x 35,0		
80 x 40,0		
80 x 45,0		
80 x 50,0		
80 x 60,0		
90 x 3,0		
90 x 4,0		
90 x 5,0		
90 x 6,0		
90 x 8,0		
90 x 10,0		
90 x 12,0		
90 x 15,0		
90 x 16,0		
90 x 20,0		
90 x 25,0		
90 x 30,0		
90 x 32,0		
90 x 40,0		
90 x 45,0		
90 x 50,0		
100 x 3,0		
100 x 4,0		
100 x 5	●	
100 x 6	●	
100 x 7		
100 x 8		
100 x 10	●	
100 x 12		
100 x 13		
100 x 14		
100 x 15		
100 x 16		
100 x 18		
100 x 20		
100 x 25		

Continuation on page 15

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
100 x 30		
100 x 32		
100 x 35		
100 x 40		
100 x 45		
100 x 50		
100 x 60		
110 x 5		
110 x 6		
110 x 8		
110 x 10		
110 x 12		
110 x 15		
110 x 20		
110 x 32		
120 x 4		
120 x 5		
120 x 6		
120 x 8		
120 x 10		
120 x 12		
120 x 14		
120 x 15		
120 x 16		
120 x 20		
120 x 22		
120 x 25		
120 x 30		
120 x 40		
120 x 50		
120 x 60		
125 x 5		
125 x 6		
125 x 8		
125 x 10		
125 x 12		
125 x 13		
125 x 15		

Continuation on page 16

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
125 x 16		
125 x 20		
125 x 25		
125 x 30		
125 x 32		
125 x 40		
125 x 50		
130 x 5		
130 x 6		
130 x 8		
130 x 10		
130 x 12		
130 x 15		
130 x 20		
130 x 25		
130 x 30		
140 x 5		
140 x 6		
140 x 8		
140 x 10		
140 x 12		
140 x 15		
140 x 16		
140 x 20		
140 x 25		
140 x 30		
140 x 32		
150 x 5		
150 x 6		
150 x 8		
150 x 10		
150 x 12		
150 x 15		
150 x 16		
150 x 20		
150 x 25		
150 x 30		
150 x 32		

Continuation on page 17

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
150 x 40		
150 x 50		
160 x 5		
160 x 6		
160 x 8		
160 x 10		
160 x 12		
160 x 15		
160 x 16		
160 x 20		
160 x 25		
160 x 30		
160 x 32		
160 x 40		
180 x 8		
180 x 10		
180 x 12		
180 x 15		
180 x 16		
180 x 20		
180 x 25		
180 x 30		
180 x 40		
200 x 5		
200 x 8		
200 x 10		
200 x 12		
200 x 15		
200 x 16		
200 x 20		
200 x 25		
200 x 30		
200 x 32		
200 x 40		
200 x 50		
250 x 10		
250 x 12		
250 x 15		

Continuation on page 18

Continuation - Flat bars, DIN EN 10277, tolerances acc. to DIN EN 10278, length approx. 3 m / 6 m

Dimension	S235JR+C/SH (St37K)	S355J0+C/SH (St52K)
250 x 20		
250 x 25		
250 x 30		
250 x 40		
250 x 50		
300 x 10		
300 x 12		
300 x 15		
300 x 20		
300 x 25		
300 x 30		
300 x 40		
300 x 50		
350 x 10		
350 x 20		
350 x 25		
350 x 30		
350 x 40		
350 x 50		
400 x 10		
400 x 20		
400 x 25		
400 x 30		
400 x 40		
400 x 50		