

Rebar according to DIN 488, grade BSt.500S (IV S)

Lengths: 12, 14, 15 und 16 m

Stock items are marked with a dot; other dimensions are available at short notice. Additional sizes, formats, and grades available on request.

Dimensions mm	Specific weight/m	Stock availability
6	0,222	
8	0,395	●
10	0,617	●
12	0,888	●
14	1,21	●
16	1,58	●
20	2,47	●
25	3,85	●
28	4,83	●

Reinforcing mesh BST 500 M according to DIN 1045-1

Reinforcement mesh may have different rib patterns (e.g. deep ribs or ribbing according to DIN 488)

Stock items are marked with a dot; other dimensions are available at short notice. Additional sizes, formats, and grades available on request.

Mesh size m	Mesh designation	Kg per m ²	Kg per mesh	Longitudinal bars mm	Transverse bars mm	Longitudinal spacing mm	Transverse spacing mm	Longitudinal steel area cm ² /m	Transverse steel area cm ² /m	Stock availability
6,00 x 2,30	Q188A	3,02	41,7	150	150	6,0	6,0	1,88	1,88	●
6,00 x 2,30	Q257A	4,12	56,8	150	150	7,0	7,0	2,57	2,57	●
6,00 x 2,30	Q335A	5,38	74,3	150	150	8,0	8,0	3,35	3,35	●
6,00 x 2,30	Q424A	6,12	84,4	150	150	9,0	9,0	4,24	4,24	●
6,00 x 2,30	Q524A	7,31	100,9	150	150	10,0	10,0	5,24	5,24	●
6,00 x 2,35	Q636A	9,36	132,0	100	125	9,0	10,0	6,36	6,28	●
6,00 x 2,30	R188A	2,43	33,6	150	250	6,0	6,0	1,88	1,13	●
6,00 x 2,30	R257A	2,99	41,2	150	250	7,0	6,0	2,57	1,13	●
6,00 x 2,30	R335A	3,64	50,2	150	250	8,0	6,0	3,35	1,13	●
6,00 x 2,30	R424A	4,87	67,2	150	250	9,0	8,0	4,24	2,01	●
6,00 x 2,30	R524A	5,49	75,7	150	250	10,0	8,0	5,24	2,01	●